UNOLUMEN®
(an entity of NORLYS Srl)


VENUS MINI RECESSED UL2811R/NPRCWB

Ground Recessed | Recessed with Lens L. 530 - Remote driver 24Vdc

IP67 IK08 III CE 500kg stop WB -20/+50°c

Linear floor-mounted recessed luminaire. Equipped with secondary optics for different types of light distribution, this Venus Mini Recessed version is particularly suited for the oblique illumination of building façades, to highlight their texture or accentuate the architectural details of historical buildings. Dali dimmable on request with extra charge.





Fixture specifications

Assembly / Usage
Inground recessed

Protection
IP 67 - IK 08

Body
Die-cast aluminium

Box
Die-cast aluminium

Frame
All glass

Screen
Tempered extra-clear glass 4mm with silk-screen printing

Seals
Gasket: neutral cross-linking silicone glue glass - Tx -50/+250°C UV resist

Screws
Stainless steel A2

Paint / Finishing
Anti-corrosive UV stabilised polyester powder

Sizes
H 60 x L 530 x W 50 x INC. 535

Electrical specifications

Power supply
24Vdc

Driver
Remote Driver 24Vdc NOT INCLUDED

Control
Remote DALI dimmable

Absorbed power
8W

Source
LED

Source flux
970 lm

Fixture source
840 lm

Apparent efficiency
87 %

Insulation class
III

Operating TA
50°

CCT LED
4000K

CRI
>80

Step MacAdam
3

Life time TM - 21
L80B10 80000h Ta 25°C

Photobiological risk
RG1

Optic distribution
Silk printed clear glass LTF>90°

Beam opening
Wide Flood/45°

Index

Index	Color	RAL
Standard	Grey	9006

Acquastop System

AcquaStop System Integrated. AcquaStop is a special process inside the product which, through different phases of resination, creates a real barrier, sealing the fixture in a definitive way and preventing the development of condensation inside it.

Accessories

ULE.CAV.540.020	Cable H05RN-F L 2mt
ULE.CAV.540.050	Cable H05RN-F L 5mt
ULE.CAV.540.100	Cable H05RN-F L 10mt
ULMOR682P/2V	Connector IP68 2Ways/2Poles L 72 x Ø 22
ULE.TRA.631	Driver 15W 24Vdc IP20 - ON/OFF L 106 x W 33 x H 22 - 1 Driver for 1 Lamp
ULE.TRA.632	Driver 70W 24Vdc IP20 - ON/OFF L 124 x W 80 x H 22 - 1 Driver for 1-8 Lamps
ULE.TRA.633	Driver 100W 24Vdc IP67 - DALI L 175 x W 63 x H 36 - 1 Driver for 1-10 Lamps
ULE.TRA.577	Driver 25W 24Vdc IP67 - ON/OFF L 14 8x W 40 x H 32 - 1 Driver for 1-2 Lamps
ULE.TRA.579	Driver 100W 24Vdc IP67 - ON/OFF L 140 x W 63 x H 32 - 1 Driver for 3-10 Lamps
ULHUB.24V.001.ND	Hub 70W 24Vdc IP66 - ON/OFF L 235 x W 200 x H 92 - 1 Hub for 1-8 Lamps
ULHUB.24V.001.DA2	Hub 70W 24Vdc IP66 - DALI-2 L 235 x W 200 x H 92 - 1 Hub for 1-8 Lamps
ULHUB.24V.001.CA	Hub 70W 24Vdc IP66 - CASAMBI L 235 x W 200 x H 92 - 1 Hub for 1-8 Lamps

Unolumen Italia Via San Pellegrino, 2, 25065 - Lumezzane Brescia - Italy UE

Please read the instructions in the manual carefully before installation. Assembly and maintenance should be carried out only by an authorized service personnel. The information in this document is subject to change without prior notice due to the dynamic development in lighting technology. Condensation, which may occur in the luminaire is a natural phenomenon and does not affect the quality of the luminaire.