




Rim, the latest addition to the Unolumen collection, is a small but performing recessed fixture with steel ring, proposed with diameters of 45 mm and 70 mm. The reduced sizes and the easy and quick installation allow its positioning in external and internal areas. In fact, Rim can be installed on floor, wall or ceiling, turning almost invisible, but insuring the created light and atmosphere to be the real main characters of the scene. The proposed beams are suitable for smooth or highlighted effects, for single or in-series installations. The ring of 316L stainless steel and the system AcquaStop for the anticondensation protection make Rim a safe and multipurpose product, ideal to give light to your fantasy.



## Fixture specifications

### Assembly / Usage

Inground or wall recessed

### Protection

IP 67 - IK 08

### Body

Anticorodal turning aluminum 6000 Serie, for greater corrosion resistance

### Box

Polypropylene (PP) 30% fiber UV Stabilized GWT750

### Frame

Stainless Steel AISI316L

### Screen

Opal glass

### Seals

Closed-cell EPDM rubber

### Sizes

H 70 x Ø 70

## Electrical specifications

### Power supply

24Vdc

### Driver

Remote Driver NOT INCLUDED

### Driver current

24Vdc

### Control

ON/OFF

### Absorbed power

6W

### Source

LED

### Source flux

690 lm

### Fixture source

70 lm

### Apparent efficiency

10 %

### Insulation class

III

### Operating TA

-20°+ 50°

### CCT LED

2700K

### CRI

80

### Step MacAdam

3

### Life time TM-21

L80B10 80000h Ta 25°C

### Optic distribution

PMMA Lens

### Beam opening

Diffuse/120°

## Index

Index	Color	RAL
Standard	Steel	-

## AcquaStop System

AcquaStop System Integrated. AcquaStop is a special process inside the product which, through different phases of resination, creates a real barrier, sealing the fixture in a definitive way and preventing the development of condensation inside it.

### Accessories

ULA.BOX.019.01	Inground formwork H 110 x Ø 135
ULD.BOX.033.01	Short formwork H 100 x Ø 60
ULE.CAV.540.020	Cable H05RN-F L 2mt
ULE.CAV.540.050	Cable H05RN-F L 5 mt
ULE.CAV.540.100	Cable H05RN-F L 10mt

ULMOR682P/2V	Connector IP68 2Ways/2Poles L 72 x Ø 22
ULE.TRA.631	Driver 15W 24Vdc IP20 - ON/OFF L 106 x W 33 x H 22 - 1 Driver for 1-2 Lamps
ULE.TRA.632	Driver 70W 24Vdc IP20 - ON/OFF L 124 x W 80 x H 22 - 1 Driver for 1-10 Lamps
ULE.TRA.577	Driver 25W 24Vdc IP67 - ON/OFF L 14 8x W 40 x H 32 - 1 Driver for 1-3 Lamps
ULE.TRA.579	Driver 100W 24Vdc IP67 - ON/OFF L 140 x W 63 x H 32 - 1 Driver for 4-14 Lamps
ULHUB.24V.001.ND	Hub 70W 24Vdc IP66 - ON/OFF L 235 x W 200 x H 92 - 1 Hub for 1-8 Lamps