




Rim, the latest addition to the Unolumen collection, is a small but performing recessed fixture with steel ring, proposed with diameters of 45 mm and 70 mm. The reduced sizes and the easy and quick installation allow its positioning in external and internal areas. In fact, Rim can be installed on floor, wall or ceiling, turning almost invisible, but insuring the created light and atmosphere to be the real main characters of the scene. The proposed beams are suitable for smooth or highlighted effects, for single or in-series installations. The ring of 316L stainless steel and the system AcquaStop for the anticondensation protection make Rim a safe and multipurpose product, ideal to give light to your fantasy.



## Index

Index	Color	RAL
00	Pure white	9016
01	Black	9005
10	White	9010
24	Bronze	-
25	Rust	-
30	Anthracite	-
35	Slate grey	-
40	Grey	9006
55	Green cool mint	6019

## Fixture specifications

<b>Assembly / Usage</b> Inground or wall recessed	<b>Frame</b> Painted Steel AISI316L
<b>Protection</b> IP 67 - IK 08	<b>Screen</b> Transparent extra-clear glass 8mm
<b>Body</b> Anticorodal turning aluminum 6000 Serie, for greater corrosion resistance	<b>Seals</b> Closed-cell EPDM rubber
<b>Box</b> Polypropylene (PP) 30% fiber UV Stabilized GWT750	<b>Paint / Finishing</b> Anti-corrosive UV stabilised polyester powder
	<b>Sizes</b> H 70 x Ø 70

## Electrical specifications

<b>Power supply</b> 24Vdc	<b>Insulation class</b> III
<b>Driver</b> Remote Driver NOT INCLUDED	<b>Operating TA</b> -20°+ 50°
<b>Driver current</b> 24Vdc	<b>CCT LED</b> 4000K
<b>Control</b> ON/OFF	<b>CRI</b> 80
<b>Absorbed power</b> 6W	<b>Step MacAdam</b> 3
<b>Source</b> LED	<b>Life time TM-21</b> L80B10 80000h Ta 25°C
<b>Source flux</b> 750 lm	<b>Optic distribution</b> PMMA Lens
<b>Fixture source</b> 534 lm	<b>Beam opening</b> Super Wide/60°
<b>Apparent efficiency</b> 71 %	

## AcquaStop System

AcquaStop System Integrated. AcquaStop is a special process inside the product which, through different phases of resination, creates a real barrier, sealing the fixture in a definitive way and preventing the development of condensation inside it.

### Accessories

ULA.BOX.019.01	Inground formwork H 110 x Ø 135	ULMOR682P/2V	Connector IP68 2Ways/2Poles L 72 x Ø 22
ULD.BOX.033.01	Short formwork H 100 x Ø 60	ULE.TRA.631	Driver 15W 24Vdc IP20 - ON/OFF L 106 x W 33 x H 22 - 1 Driver for 1-2 Lamps
ULE.CAV.540.020	Cable H05RN-F L 2mt	ULE.TRA.632	Driver 70W 24Vdc IP20 - ON/OFF L 124 x W 80 x H 22 - 1 Driver for 1-10 Lamps
ULE.CAV.540.050	Cable H05RN-F L 5 mt	ULE.TRA.577	Driver 25W 24Vdc IP67 - ON/OFF L 14 8x W 40 x H 32 - 1 Driver for 1-3 Lamps
ULE.CAV.540.100	Cable H05RN-F L 10mt	ULE.TRA.579	Driver 100W 24Vdc IP67 - ON/OFF L 140 x W 63 x H 32 - 1 Driver for 4-14 Lamps
		ULHUB.24V.001.ND	Hub 70W 24Vdc IP66 - ON/OFF L 235 x W 200 x H 92 - 1 Hub for 1-8 Lamps