




Zeus 70 is the new line of steplight with grazing light born to create suggestive light and shadow effects, available in diameters of 45 mm and 70 mm. Design to give life to residential and public walk ways, also available with dedicated wall and ceiling version , making itself almost invisible but keeping light and atmosphere created the main characters of the scene. With one, two or four slots , Zeus 70 becomes a perfect fixture for soft or strong effects, for single or series installations. IP67 degree protection combined with AcquaStop system for anti-condensation protection make Zeus 70 a reliable and safe product, to inspire light emotions.



## Fixture specifications

### Assembly / Usage

Inground or wall recessed

### Protection

IP 67 - IK 08

### Body

Anticorodal turning aluminum 6000 Serie, for greater corrosion resistance

### Box

Polypropylene (PP) 30% fiber UV Stabilized GWT750

### Screen

Transparent Polycarbonate

### Seals

Closed-cell EPDM rubber

### Paint /finishing

Anti-corrosive UV stabilised polyester powder

### Sizes

H 85 x Ø 70

## Electrical specifications

### Power supply

max 500mA

### Driver

Remote Driver NOT INCLUDED

### Control

Remote DALI dimmable

### Absorbed power

6W

### Source

LED

### Source flux

750 lm

### Fixture source

45 lm

### Apparent efficiency

6 %

### Insulation class

III

### Operating TA

-20°+ 50°

### CCT LED

4000K

### CRI

80

### Step MacAdam

3

### Optic distribution

PMMA Lens

### Beam opening

Diffused 1 window

## Index

Index	Color	RAL
00	Pure white	9016
01	Black	9005
10	White	9010
24	Bronze	-
25	Rust	-
30	Anthracite	-
35	Slate grey	-
40	Grey	9006
55	Green cool mint	6019

## Acquastop System

AcquaStop System Integrated. AcquaStop is a special process inside the product which, through different phases of resination, creates a real barrier, sealing the fixture in a definitive way and preventing the development of condensation inside it.

## Accessories

ULA.BOX.019.01	Inground formwork H 110 x Ø 135	ULE.TRA.634.500	Driver 60W 500mA IP20 - ON/OFF L 124 x W 80 x H 22 - 1 Driver for 1-5 Lamps
ULD.BOX.033.01	Short formwork H 100 x Ø 60	ULE.TRA.635.500	Driver 60W 500mA IP20 - DALI2 L 124 x W 80 x H 22 - 1 Driver for 1-5 Lamps
ULE.CAV.540.020	Cable H05RN-F L 2mt	ULE.TRA.636.500	Driver 60W 500mA IP20 - CASAMBI L 124 x W 80 x H 22 - 1 Driver for 1-5 Lamps
ULE.CAV.540.050	Cable H05RN-F L 5 mt	ULE.TRA.553.500	Driver 20W 500mA IP67 - ON/OFF L 120 x W 38 x H 25 - 1 Driver for 1-3 Lamps
ULE.CAV.540.100	Cable H05RN-F L 10mt	ULE.TRA.584.500	Driver 30W 500mA IP68 - DALI2 L 121 x W 53 x H 26 - 1 Driver for 1-3 Lamps
ULMOR682P/2V	Connector IP68 2Ways/2Poles L 72 x Ø 22	ULHUB.500.001.ND	Hub 500mA IP66 - ON/OFF with driver 60W IP20 L 235 x W 200 x H 92 - 1 Hub for 1-5 Lamps
ULE.TRA.621.500	Driver 20W 500mA IP20 - ON/OFF L 111 x W 52 x H 22 - 1 Driver for 1-3 Lamps	ULHUB.500.001.DA2	Hub 500mA IP66 - DALI-2 with driver 60W IP20 L 235 x W 200 x H 92 - 1 Hub for 1-5 Lamps
ULE.TRA.623.500	Driver 36W 500mA IP20 - ON/OFF L 163 x W 30 x H 21 - 1 Driver for 1-4 Lamps	ULHUB.500.001.CA	Hub 500mA IP66 - CASAMBI with driver 60W IP20 L 235 x W 200 x H 92 - 1 Hub for 1-5 Lamps