


ZEUS 70 UL4070R/WRCC2L Ground Recessed | Recessed 2 windows Ø70 - Remote driver max 500mA



Zeus 70 is the new line of steplight with grazing light born to create suggestive light and shadow effects, available in diameters of 45 mm and 70 mm. Design to give life to residential and public walk ways, also available with dedicated wall and ceiling version , making itself almost invisible but keeping light and atmosphere created the main characters of the scene. With one, two or four slots , Zeus 70 becomes a perfect fixture for soft or strong effects, for single or series installations. IP67 degree protection combined with AcquaStop system for anti-condensation protection make Zeus 70 a reliable and safe product, to inspire light emotions.





Index

Index	Color	RAL
00	Pure white	9016
01	Black	9005
10	White	9010
24	Bronze	-
25	Rust	-
30	Anthracite	-
35	Slate grey	-
40	Grey	9006
55	Green cool mint	6019

Fixture specifications

Assembly / Usage			
Inground or wall recessed			
Protection			
IP 67 - IK 08			

Body

Anticorodal turning aluminum 6000 Serie, for greater corrosion resistance

Вох

Power max 5

Driver

Remo Contro Remo Absor 6W

Sourc LED

Sourc 690 In Fixture 77 Im Appar 11 %

Polypropylene (PP) 30% fiber UV Stabilized GWT750

Electrical specifications

r supply	Insulation class	
500mA		
r	Operating TA	
ote Driver NOT INCLUDED	-20°+ 50°	
rol	CCT LED	
ote DALI dimmable	3000K	
rbed power	CRI	
	80	
ce	Step MacAdam	
	3	
ce flux	Optic distribution	
n	PMMA Lens	
re source	Beam opening	
	Diffused 2 window	
rent efficiency		

Screen

Seals

Sizes

H 85 x Ø 70

Transparent Polycarbonate

Anti-corrosive UV stabilised polyester powder

Closed-cell EPDM rubber
Paint /finishing

Acquastop System

AcquaStop System Integrated. AcquaStop is a special process inside the product which, through different phases of resination, creates a real barrier, sealing the fixture in a definitive way and preventing the development of condensation inside it.

Accessories

ULA.BOX.019.01	Inground formwork H 110 x Ø 135	ULE.TRA.634.500	Driver 60W 500mA IP20 - ON/OFF L 124 x W 80 x H 22 - 1 Driver for 1-5 Lamps
ULD.BOX.033.01	Short formwork H 100 x Ø 60	ULE.TRA.635.500	Driver 60W 500mA IP20 - DALI2 L 124 x W 80 x H 22 - 1 Driver for 1-5 Lamps
ULE.CAV.540.020	Cable H05RN-F L 2mt	ULE.TRA.636.500	Driver 60W 500mA IP20 - CASAMBI L 124 x W 80 x H 22 - 1 Driver for 1-5 Lamps
ULE.CAV.540.050	Cable H05RN-F L 5 mt	ULE.TRA.553.500	Driver 20W 500mA IP67 - ON/OFF L 120 x W 38 x H 25 - 1 Driver for 1-3 Lamps
JLE.CAV.540.100	Cable H05RN-F L 10mt	ULE.TRA.584.500	Driver 30W 500mA IP68 - DALI2 L 121 x W 53 x H 26 - 1 Driver for 1-3 Lamps
ULMOR682P/2V	Connector IP68 2Ways/2Poles	ULHUB.500.001.ND	Hub 500mA IP66 - ON/OFF with driver 60W IP20 L 235 x W 200 x H 92 - 1 Hub for 1-5 Lamps
ULE.TRA.621.500	Driver 20W 500mA IP20 - ON/OFF L 111 x W 52 x H 22 - 1 Driver for 1-3 Lamps	ULHUB.500.001.DA2	Hub 500mA IP66 - DALI-2 with driver 60W IP20 L 235 x W 200 x H 92 - 1 Hub for 1-5 Lamps
ULE.TRA.623.500	Driver 36W 500mA IP20 - ON/OFF L 163 x W 30 x H 21 - 1 Driver for 1-4 Lamps	ULHUB.500.001.CA	Hub 500mA IP66 - CASAMBI with driver 60W IP20 L 235 x W 200 x H 92 - 1 Hub for 1-5 Lamps

Unolumen Italia Via San Pellegrino, 2, 25065 - Lumezzane Brescia - Italy UE

Please read the instructions in the manual carefully before installation. Assembly and maintenance should be carried out only by an authorized service personnel. The information in this document is subject to change without prior notice due to the dynamic development in lighting technology. Condensation, which may occur in the luminaire is a natural phenomenon and does not affect the quality of the luminaire.