UNOLUMEN®
(an entity of NORLYS Srl)

CHESTER 250 ULILCH361540

36W adjustable LED ground recessed light

IP67 | CRI ≥80 | CE | RoHS | -20/+55°C | 50K HRS | 5 YEARS WARRANTY



Type of luminaire

Type of luminarire
Compact IP67 corrosion resistant recessed structure with uniform light output


General information

Material
Stainless steel + tempered glass + High purity aluminium

Mounting Method
Ground recessed

Type of light source
SMD LED

Luminaire dimension (mm)
Ø250 X H190mm



Technical data

System power
36W

Luminaire efficacy
80lm/W

Rated luminous flux
2956lm

Color temperature
4000K

Class
III

Beam angle
15°

Source
LED

Color Rendering Index (CRI)
>80

Power supply
12V/24V DC

Accessories
Supplied with cable of 2x0.5m & installation sleeve

Control
on/off

Power factor
>0.9

Rated life at 25°C
50,000H

Total Harmonic Distortion (THD)
<10%

Ambient temperature (Ta)
25°C

Max. ambient temperature
50°C

Ingress Protection rating (IP)
IP67

Conformity mark
CE, RoHS

Index

Index	Color	RAL
Standard	steel	-

Accessories and options

ULILCH361540-QP	Quick plug connection
ULILCH361540-CRI90	CRI≥90
ULILCH361540-DALI	DALI dimming
ULILCH361540-RGBW	RGBW

Installation manual | Photometric IES files | Photometric LDT files

Unolumen Italia Via San Pellegrino, 2, 25065 - Lumezzane Brescia - Italy EU

Please read the instructions in the manual carefully before installation. Assembly and maintenance should be carried out only by an authorized service personnel. The information in this document is subject to change without prior notice due to the dynamic development in lighting technology. Condensation, which may occur in the luminaire is a natural phenomenon and does not affect the quality of the luminaire.