UNOLUMEN®
(an entity of NORLYS Srl)

TORINO 80 ULILTO724RGBW

IP67 corrosion resistant inground light

24° | IP67 | CRI ≥80 | CE | RoHS | -20/+50°C | 50K HRS | 5 YEARS WARRANTY



Type of luminaire

Type of luminarire
Compact IP67 corrosion resistant recessed structure with uniform light output


General information

Material
Stainless steel + tempered glass + High purity aluminium

Mounting Method
Ground recessed

Type of light source
Bridgelux COB

Luminaire dimension (mm)	Outer Dia (mm)	Cut out Dia (mm)
Ø80 X H95mm	Ø80mm	Ø71mm



Technical data

System power
7W

Luminaire efficacy
80lm/W

Rated luminous flux
RGBW - 256lm
Red - 38lm
Green - 98lm
Blue - 25lm
White - 105lm

Color temperature
RGBW

Class
III

Beam angle
24°

Source
LED

Color Rendering Index (CRI)
>80

Power supply
12V/24V DC

Accessories
Supplied with cable of 2x0.5m & installation sleeve

Control
Remote on/off

Power factor
>0.9

Rated life at 25°C
50,000H

Total Harmonic Distortion (THD)
<10%

Ambient temperature (Ta)
25°C

Max. ambient temperature
50°C

Ingress Protection rating (IP)
IP67

Conformity mark
CE, RoHS

Index

Index	Color	RAL
Standard	steel	-

Accessories and options

ULILTO724RGBW-QP	Quick plug connection
ULILTO724RGBW-CRI90	CRI≥90
ULILTO724RGBW-DALI	DALI dimming

Installation manual | Photometric IES files | Photometric LDT files

Unolumen Italia Via San Pellegrino, 2, 25065 - Lumezzane Brescia - Italy EU

Please read the instructions in the manual carefully before installation. Assembly and maintenance should be carried out only by an authorized service personnel. The information in this document is subject to change without prior notice due to the dynamic development in lighting technology. Condensation, which may occur in the luminaire is a natural phenomenon and does not affect the quality of the luminaire.