
UNOLUMEN®
(an entity of NORLYS Srl)

ZIA 160 ULILZI183027

IP67 corrosion resistant inground light

IP67 · CRI ≥80 · CE · RoHS · -20/+50°c · DC-IN · 50K HRS · 5 YEARS WARRANTY





Type of luminaire

Type of luminarire
Compact IP67 corrosion resistant recessed structure with uniform light output

General information

Material
Stainless steel + tempered glass + High purity aluminium

Mounting Method
Ground recessed

Type of light source
SMD LED

Luminaire dimension (mm)
Ø160 X H153mm

Technical data

System power 18W	**Accessories** Supplied with cable of 2x0.5m & installation sleeve
Luminaire efficacy 80lm/W	**Control** Remote on/off
Rated luminous flux 1296lm	**Power factor** >0.9
Color temperature 2700K	**Rated life at 25°C** 50,000H
Class III	**Total Harmonic Distortion (THD)** <10%
Beam angle 30°	**Ambient temperature (Ta)** 25°C
Source LED	**Max. ambient temperature** 50°C
Color Rendering Index (CRI) >80	**Ingress Protection rating (IP)** IP67
Power supply 12V/24V DC	**Conformity mark** CE, RoHS

Index

Index	Color	RAL
Standard	steel	-

Accessories and options

ULILZI183027-QP	Quick plug connection	ULILZI183027-R	Red color
ULILZI183027-CRI90	CRI≥90	ULILZI183027-G	Green color
ULILZI183027-DALI	DALI dimming	ULILZI183027-B	Blue color
		ULILZI183027-RGBW	RGBW

Installation manual | Photometric IES files | Photometric LDT files

Unolumen Italia Via San Pellegrino, 2, 25065 - Lumezzane Brescia - Italy EU

Please read the instructions in the manual carefully before installation. Assembly and maintenance should be carried out only by an authorized service personnel. The information in this document is subject to change without prior notice due to the dynamic development in lighting technology. Condensation, which may occur in the luminaire is a natural phenomenon and does not affect the quality of the luminaire.