



Type of luminaire

Type of luminaire
Compact and seamless

General information

Material
Sheet steel

Mounting Method
Recessed

Type of light source
LED

Light control
On/off

Luminaire dimension (mm)
L595 x W595 x H50

Technical data

LED mode
SMD 2835

System power
25W

System efficiency
120 lm/W

Rated luminous flux
3060lm

Color temperature
5000K

SDCM
<3

Unified Glare Rating (UGR)
<19

Beam angle
36°

Color Rendering Index (CRI)
≥80

Driver
External

Control
on/off

Power factor
>0.9

Rated life at 25°C
L80/B20

Total Harmonic Distortion (THD)
<15%

Ambient temperature (Ta)
25°C

Max. ambient temperature
40°C

Operating voltage
220-240V AC

Ingress Protection rating (IP)
IP20

Conformity mark
CE, RoHS

Index

Index	Color	RAL
Standard	white	9016

Accessories and options

ULPLOS2550OPA-SM	Surface Mount Kit	ULPLOS2550OPA-DALI	Dali dimming
ULPLOS2550OPA-PM	Pendant Mount Kit	ULPLOS2550OPA-PUSH	Push dimming
		ULPLOS2550PRA	Prismatic diffuser

[↓ Installation manual](#)

[↓ Photometric IES files](#)

[↓ Photometri LDT files](#)