



## Type of luminaire

**Type of luminaire**  
Compact and seamless

## General information

**Material**  
Sheet steel

**Mounting Method**  
Recessed

**Type of light source**  
LED

**Light control**  
On/off

**Luminaire dimension (mm)**  
L595 x W595 x H50

## Technical data

**LED mode**  
SMD 2835

**System power**  
30W

**System efficiency**  
120 lm/W

**Rated luminous flux**  
3444lm

**Color temperature**  
3000K

**SDCM**  
<3

**Unified Glare Rating (UGR)**  
<19

**Beam angle**  
36°

**Color Rendering Index (CRI)**  
≥80

**Driver**  
External

**Control**  
on/off

**Power factor**  
>0.9

**Rated life at 25°C**  
L80/B20

**Total Harmonic Distortion (THD)**  
<15%

**Ambient temperature (Ta)**  
25°C

**Max. ambient temperature**  
40°C

**Operating voltage**  
220-240V AC

**Ingress Protection rating (IP)**  
IP20

**Conformity mark**  
CE, RoHS

## Index

Index	Color	RAL
Standard	white	9016

### Accessories and options

ULPLOS3030OPA-SM	Surface Mount Kit	ULPLOS3030OPA-DALI	Dali dimming
ULPLOS3030OPA-PM	Pendant Mount Kit	ULPLOS3030OPA-PUSH	Push dimming
		ULPLOS3030PRA	Prismatic diffuser

[↓ Installation manual](#)

[↓ Photometric IES files](#)

[↓ Photometri LDT files](#)