



Type of luminaire

Type of luminare

Compact and seamless

General information

Material

Sheet steel

Mounting Method

Recessed

Type of light source

LED

Light control

On/off

Luminaire dimension (mm)

L1195 x W295 x H50

Technical data

LED mode

SMD 2835

System power

30W

System efficiency

120 lm/W

Rated luminous flux

3621lm

Color temperature

5000K

SDCM

<3

Unified Glare Rating (UGR)

<19

Beam angle

36°

Color Rendering Index (CRI)

≥80

Driver

External

Control

on/off

Power factor

>0.9

Rated life at 25°C

L80/B20

Total Harmonic Distortion (THD)

<15%

Ambient temperature (Ta)

25°C

Max. ambient temperature

40°C

Operating voltage


220-240V AC

Ingress Protection rating (IP)

IP20

Conformity mark

CE, RoHS



Index

Index	Color	RAL
Standard	white	9016

Accessories and options

ULPLOS3050OPB-SM	Surface Mount Kit	ULPLOS3050OPB-DALI	Dali dimming
ULPLOS3050OPB-PM	Pendant Mount Kit	ULPLOS3050OPB-PUSH	Push dimming
		ULPLOS3050PRB	Prismatic diffuser

↓ Installation manual

↓ Photometric IES files

↓ Photometri LDT files