

## Type of luminaire

**Type of luminaire**  
Compact and seamless

## General information

**Material**  
Aluminium

**Mounting Method**  
Recessed

**Type of light source**  
LED

**Light control**  
Non-dimmable, on/off

**Luminaire dimension (mm)**  
L595 x W595 x H32

## Technical data

**LED mode**  
SMD 2835

**System power**  
30W

**System efficiency**  
120 lm/W

**Rated luminous flux**  
3600lm

**Color temperature**  
3000K

**SDCM**  
<5

**Unified Glare Rating (UGR)**  
<19

**Beam angle**  
120°

**Color Rendering Index (CRI)**  
>80

**Driver**  
1-10V

**Control**  
Non-dimmable

**Power factor**  
>0.95

**Rated life at 25°C**  
L80/B10

**Total Harmonic Distortion (THD)**  
<15%



**Ambient temperature (Ta)**  
25°C

**Max. ambient temperature**  
35°C

**Operating voltage**  
220-240V AC

**Ingress Protection rating (IP)**  
IP44

**Conformity mark**  
CE, RoHS



### Accessories and options

ULPLSO30xx	On/off
ULPLSO30xx-EM	Remote Emergency Pack
ULPLSO30xx-DALI	DALI Dimmable

xx - Selection of color temperature

## Index

Index	Color	RAL
Standard	white	9016

Manual

Photometric IES files

Photometri LDT files