

Sole compact and seamless

-`©́.-UGR < 19

CRI

> 80

:84:

IP44

120





Type of luminaire

CE

RoHS

Type of luminarire Compact and seamless

General information

| General mornation |
|--------------------------|
| Material |
| Aluminium |
| Mounting Method |
| Recessed |
| Type of light source |
| LED |
| Light control |
| Non-dimmable, on/off |
| Luminaire dimension (mm) |
| L595 x W595 x H32 |
| |

SOK HRS

5 Salar

ARR

 \mathcal{P}

220-240V

8

15/ +35 c

Technical data

| LED mode SMD 2835 |
|------------------------------------|
| System power 30W |
| System efficiency 120 lm/W |
| Rated luminous flux 3600lm |
| Color temperature 4000K |
| SDCM <5 |
| Unified Glare Rating (UGR) <19 |
| Beam angle 120° |
| Color Rendering Index (CRI) >80 |
| Driver |

1-10V

Accessories and options

| On/off |
|-----------------------|
| Remote Emergency Pack |
| DALI Dimmable |
| |

| Control |
|--------------|
| Non-dimmable |
| |
| Power factor |

Rated life at 25°C L80/B10 Total Harmonic Distortion (THD)

- <15%
- Ambient temperature (Ta) 25°C
- Max. ambient temperature
- 35°C
- Operating voltage 220-240V AC

Ingress Protection rating (IP)

IP44 Conformity mark

CE, ROHS

Index


| Index | Color | RAL |
|----------|-------|------|
| Standard | white | 9016 |


| 🗄 Manual | 🛓 Photometric IES files | 🕹 Photometri LDT files |
|----------|-------------------------|------------------------|
| | | |


Unolumen Italia Via San Pellegrino, 2, 25065 - Lumezzane Brescia - Italy UE

Please read the instructions in the manual carefully before installation. Assembly and maintenance should be carried out only by an authorized service personnel. The information in this document is subject to change without prior notice due to the dynamic development in lighting technology. Condensation, which may occur in the luminaire is a natural phenomenon and does not affect the quality of the luminaire.









xx - Selection of color temperature