



Type of luminaire

Type of luminaire

Compact and seamless

General information

Material

Aluminium

Mounting Method

Recessed

Type of light source

LED

Light control

Non-dimmable, on/off

Luminaire dimension (mm)

L1195 x W295 x H32

Technical data

LED mode

SMD 2835

System power

30W

System efficiency

120 lm/W

Rated luminous flux

3672lm

Color temperature

6000K

SDCM

<5

Unified Glare Rating (UGR)

<19

Beam angle

120°

Color Rendering Index (CRI)

>80

Driver

on/off

Control

Non-dimmable

Power factor

>0.95

Rated life at 25°C

50,000 hrs

Total Harmonic Distortion (THD)

<15%

Ambient temperature (Ta)

25°C

Max. ambient temperature

35°C

Operating voltage

220-240V AC

Ingress Protection rating (IP)

IP44

Conformity mark

CE, RoHS

Accessories and options

ULPLSO3123040-SM	Surface Mount Kit
ULPLSO3123040-SK	Suspension Kit

ULPLSO3123040-110	1-10V Dimming
ULPLSO3123040-EM	Remote Emergency Pack
ULPLSO3123040-DALI	DALI Dimmable

Index

Index	Color	RAL
Standard	white	9016

↓ Installation manual	↓ Photometric IES files	↓ Photometric LDT files
---------------------------------------	---	---