



Type of luminaire

Type of luminaire
Compact and seamless

General information

Materials
Aluminium + PMMA + PS

Mounting Method
Recessed

Type of light source
LED

Light control
Non-dimmable, on/off

Luminaire dimension (mm)
L595 x W595 x H28

Technical data

LED mode
SMD 2835

System power
36W

System efficiency
130lm/W

Rated luminous flux
4540lm

Color temperature
3000K

IK Rating
IK05

SDCM
<5

Unified Glare Rating (UGR)
<19

Beam angle
120°

Color Rendering Index (CRI)
>80

Driver
on/off

Control
Non-dimmable

Power factor
>0.95

Rated life at 25°C
L70/B50

Total Harmonic Distortion (THD)
<15%

Ambient temperature (Ta)
25°C

Max. ambient temperature
35°C

Operating voltage
220-240V AC

Ingress Protection rating (IP)
IP65/IP40

Conformity mark
CE, RoHS

Accessories and options

ULPLSOIP3630-SM	Surface Mount Kit
ULPLSOIP3630-SK	Suspension Kit

ULPLSOIP3630-I10	1-10V Dimming
ULPLSOIP3630-EM	Remote Emergency Pack
ULPLSOIP3630-DALI	DALI Dimmable
ULPLSOIP3630MS	Motion sensor
ULPLSOIP3630DS	Daylight sensor

Index

Index	Color	RAL
Standard	white	9016

↓ Installation manual

↓ Photometric IES files

↓ Photometri LDT files

