



Type of luminaire

Type of luminaire

Compact and seamless

General information

Material

Aluminium

Mounting Method

Recessed

Type of light source

LED

Light control

Non-dimmable, on/off

Luminaire dimension (mm)

L595 x W595 x H32

Technical data

LED mode

SMD 2835

System power

30W

System efficiency

140 lm/w

Rated luminous flux

4074lm

Color temperature

3000K

IK Rating

IK05

SDCM

<5

Unified Glare Rating (UGR)

<19

Beam angle

120°

Color Rendering Index (CRI)

>80

Driver

on/off

Control

Non-dimmable

Power factor

>0.95

Rated life at 25°C

L80/B10

Total Harmonic Distortion (THD)

<15%

Ambient temperature (Ta)

25°C

Max. ambient temperature

35°C

Operating voltage

220-240V AC

Ingress Protection rating (IP)

IP44

Conformity mark

CE, RoHS

Accessories and options

ULPLSOPRO3030-SM	Surface Mount Kit
ULPLSOPRO3030-SK	Suspension Kit

ULPLSOPRO3030-110	1-10V Dimming
ULPLSOPRO3030-EM	Remote Emergency Pack
ULPLSOPRO3030-DALI	DALI Dimmable

Index

Index	Color	RAL
Standard	white	9016

↓ Installation manual	↓ Photometric IES files	↓ Photometri LDT files
---------------------------------------	---	--

