



## Type of luminaire

### Type of luminaire

Compact and seamless

## General information

### Material

Aluminium

### Mounting Method

Recessed

### Type of light source

LED

### Light control

Non-dimmable, on/off

### Luminaire dimension (mm)

L595 x W595 x H32

## Technical data

### LED mode

SMD 2835

### System power

30W

### System efficiency

140 lm/w

### Rated luminous flux

4284lm

### Color temperature

6000K

### IK Rating

IK05

### SDCM

<5

### Unified Glare Rating (UGR)

<19

### Beam angle

120°

### Color Rendering Index (CRI)

>80

### Driver

on/off

### Control

Non-dimmable

### Power factor

>0.95

### Rated life at 25°C

L80/B10

### Total Harmonic Distortion (THD)

<15%

### Ambient temperature (Ta)

25°C

### Max. ambient temperature

35°C

### Operating voltage

220-240V AC

### Ingress Protection rating (IP)

IP44

### Conformity mark

CE, RoHS

## Accessories and options

ULPLSOPRO3060-SM	Surface Mount Kit
ULPLSOPRO3060-SK	Suspension Kit

ULPLSOPRO3060-I10	1-10V Dimming
ULPLSOPRO3060-EM	Remote Emergency Pack
ULPLSOPRO3060-DALI	DALI Dimmable

## Index

Index	Color	RAL
Standard	white	9016

↓ Installation manual

↓ Photometric IES files

↓ Photometri LDT files