


CADICE ULSDCA201527R Diecast aluminium body with high quality reflector







Type of luminaire

Type of luminarire

LED surface mounted downlight

General information

Material	
Die-cast aluminium	
Mounting Method	
Surface mount	
Type of light source	
LED	
Light control	
On/off	
Luminaire dimension (mm)	Outer Dia

Ø 135 x W193

Outer Dia Ø 135

Technical data

ED mode	Control	
ED	on/off	
System power	Power factor	
20W	>0.9	
System efficiency	Rated life at 25°C	
90 lm/W	50,000 hrs	
Rated luminous flux 800lm	Total Harmonic Distortion (THD)	
Color temperature	Ambient temperature (Ta)	
2700K	25°C	
Class	Max. ambient temperature 40°C	
ЭСМ	Operating voltage	
3	220-240V AC	
Seam angle 5°	Ingress Protection rating (IP)	
Color Rendering Index (CRI)	Shape	
90	Round	
river	Conformity mark	
uilt-in	CE, ROHS	

Color finish options

Code	Color	Accessories and options	
ULSDCA201527R-MW	Matt white	ULSDCA201527R-DALI	Dali dimming
ULSDCA201527R-MB	Matt black	ULSDCA201527R-010	0-10V Dimming

ightarrow Installation n

2 Photometric IES file

↓ Photometri LDT files

Unolumen Italia Via San Pellegrino, 2, 25065 - Lumezzane Brescia - Italy UE

Please read the instructions in the manual carefully before installation. Assembly and maintenance should be carried out only by an authorized service personnel. The information in this document is subject to change without prior notice due to the dynamic development in lighting technology. Condensation, which may occur in the luminaire is a natural phenomenon and does not affect the quality of the luminaire.