



## Type of luminaire

### Type of luminaire

LED surface mounted downlight

## General information

### Material

Die-cast aluminium

### Mounting Method

Surface mount

### Type of light source

LED

### Light control

On/off

### Luminaire dimension (mm)

L135 x H135 x W193

## Technical data

### LED mode

LED

### System power

20W

### System efficiency

90 lm/W

### Rated luminous flux

1873lm

### Color temperature

5000K

### Class

III

### SDCM

<3

### Beam angle

24°

### Color Rendering Index (CRI)

≥90

### Driver

Built-in

### Control

on/off

### Power factor

>0.9

### Rated life at 25°C

50,000 hrs

### Total Harmonic Distortion (THD)

<15%

### Ambient temperature (Ta)

25°C

### Max. ambient temperature

40°C

### Operating voltage

220-240V AC

### Ingress Protection rating (IP)

IP20

### Shape

Square

### Conformity mark

CE, RoHS

## Color finish options

Code	Color
ULSDCA202450S-MW	Matt white
ULSDCA202450S-MB	Matt black

### Accessories and options

ULSDCA202450S-DALI	Dali dimming
ULSDCA202450S-010	0-10V Dimming

↓ Installation manual

↓ Photometric IES files

↓ Photometri LDT files