



Type of luminaire

Type of luminaire
LED surface mounted downlight

General information

Material
Die-cast aluminium

Mounting Method
Surface mount

Type of light source
LED

Light control
On/off

Luminaire dimension (mm)
Ø 160 x W220

Outer Dia
Ø 160

Technical data

LED mode
LED

System power
28W

System efficiency
90 lm/W

Rated luminous flux
260lm

Color temperature
5000K

Class
III

SDCM
<3

Beam angle
15°

Color Rendering Index (CRI)
≥90

Driver
Built-in

Control
on/off

Power factor
>0.9

Rated life at 25°C
50,000 hrs

Total Harmonic Distortion (THD)
<15%

Ambient temperature (Ta)
25°C

Max. ambient temperature
40°C

Operating voltage
220-240V AC

Ingress Protection rating (IP)
IP20

Shape
Round

Conformity mark
CE, RoHS

Color finish options

Code	Color
ULSDCA281550R-MW	Matt white
ULSDCA281550R-MB	Matt black

Accessories and options

ULSDCA281550R-DALI	Dali dimming
ULSDCA281550R-010	0-10V Dimming

↓ Installation manual	↓ Photometric IES files	↓ Photometri LDT files
---------------------------------------	-----------------------------------------	----------------------------------------